COMPRESSOR/LIMITER CL9

Classic Compressor/Limiter Effects Pedal

Thank you for showing your confidence in us by purchasing the BEHRINGER COMPRESSOR/LIMITER CL9. This ultimate effects pedal is specifically designed to achieve super-smooth compression and extended sustain. Thanks to its high-performance features you can compress loud and boost low signals without degrading the original sound.

A compressor limits the dynamic range of a signal. This means that signal peaks will be attenuated and the level differences between loudest and softest playing are reduced. This results in a more powerful tone.

1. Controls



- The **ATTACK TIME** control determines how fast the compressor responds to input signal peaks.
- 2 The **LEVEL** control adjusts the output level.
- 3 The **SUSTAIN** control determines the amount of compression.
- The ON/BATT LED illuminates when the effect is activated. It also serves as a battery level indicator.
- Use the footswitch to activate/deactivate the effect.
- 6 Use this 1/4" TS **IN** connector to plug in the instrument cable.
- The ¼" TS OUT connector sends the signal to your amp.

Use the **DC IN** connection to plug in a 9 V power supply (not included).

The **BATTERY COMPARTMENT** is located underneath the pedal cover. To install or replace the 9 V battery (not included), press the hinges with a ballpoint pen and remove the pedal cover. Be careful not to scratch the unit.



The CL9 has no on/off switch. As soon as you insert the plug into the in connector, the CL9 is on. When not in use, remove the plug from the in connector. This extends the life of the battery.

The **SERIAL NUMBER** is located at the underside.

2. Safety Instructions

Do not use near water, or install near heat sources. Use only authorized attachments/accessories. Do not service product yourself. Contact our qualified servicing personnel for servicing or repairs, especially when power supply cord or plug is damaged.

3. Warranty

Please register your new BEHRINGER equipment right after your purchase by visiting http://behringer.com and read the terms and conditions of our warranty carefully.

4. Specifications

Japan

In	
Connector	1⁄4" TS
Impedance	500 kΩ
Out	
Connector	1⁄4" TS
Impedance	1 kΩ
Power Supply	
	9 V ··· , 100 mA regulated
BEHRINGER PSU-	-SB
USA/Canada	120 V~, 60 Hz
Europe/U.K./ Australia	230 V~, 50 Hz
China	220 V∼, 50 Hz
Korea	220 V~, 60 Hz

100 V~, 50/60 Hz

Power connector	2 mm DC jack,
	negative center
Battery	9 V type 6LR61
Power consumption	30 mA

Physical/Weight	
Dimensions (H x W x D)	approx. 2 % x 2 % x 4 %" approx. 54 x 70 x 123 mm
Weight	approx. 0.73 lbs / 0.33 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may therefore differ from those listed or shown.

TECHNICAL SPECIFICATIONS AND APPEARANCES ARE SUBJECT TO CHANGE WITHOUT NOTICE AND ACCURACY IS NOT GUIARANTEED. BEHRINGER IS PART OF THE MUSIC GROUP (MUSIC-GROUP COMP. ALL TRADEMARKS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. MUSIC GROUP ACCEPTS NO LIABILITY FOR ANY LOSS WHICH MAY BE SUFFERED BY ANY PERSON WHO RELIES EITHER WHOLLY OR IN PART UPON ANY DESCRIPTION, PHOTOGRAPH OR STATEMENT CONTAINED HERRIC. COLORS AND SPECIFICATIONS MAY VARY FROM ACTUAL PRODUCT. MUSIC GROUP PRODUCTS ARE SOLD THROUGH AUTHORIZED FULLFILLERS AND RESELLERS ONLY. FULLFILLERS AND RESELLERS ARE NOT AGENTS OF MUSIC GROUP PAND HAVE ABSOLUTELY NO AUTHORITY TO BIND MUSIC GROUP BY ANY EXPRESS OR IMPLIED UNDERTRAINS OR REPRESENTATION. THIS MANUAL IS COPYRIGHTED. NO PART OF THIS MANUAL MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING AND RECORDING OF ANY KIND, FOR ANY PURPOSE, WITHOUT THE EXPRESS WRITTED IN ANY FORM SECOND OF MUSIC GROUP IP LTD. ALL RIGHTS RESERVED. © 2012 MUSIC Group IP Ltd. Trident Chambers, Wickhams Cay, P.O. Box 146, Road Town, Tortola, British Virgin Islands

