



JS-22

Order No.: 23.1970

EUR 139,90

RRP *

PRODUCTINFOS

Professional condenser microphone,

for studio applications and live performances. Ideally suited for direct or overhead sound pick-up of acoustic instruments, percussions and vocals or 2 x JS-22 for high-quality studio recordings.

- Extra thin gold-plated 1.25 cm (½") cone
- Low cut switch (80 Hz)
- 10 dB attenuation, switchable
- 48 V phantom power
- Robust brass body of high quality
- Supplied accessories: robust hard-sided case, microphone windshield and microphone holder

TECHNICAL SPECIFICATIONS

Type	condenser microphone
Transmission method	cable

Pick-up pattern	cardioid
System	condenser
Carrier frequency range	-
Transmitting power	-
Power supply	-
Operating time	-
Audio frequency range	20-20,000 Hz
Nominal impedance	100 Ω
Sensitivity	15.8 mV/Pa
S/N ratio	78 dB
Maximum sound pressure	140 Ω
Power supply	DC 48 V, phantom power
Gooseneck length	
Material (housing/cabinet)	brass
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 20 mm x 150 mm
Weight	130 g
Cable	-
Connection	XLR, bal.

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.