







HIGH PERFORMANCE AD/DA INTERFACE & MONITORING SYSTEM



DISCOVER YOUR **iD**ENTITY

-  **WORLD CLASS FRONT END**  
2 x *audient* discrete class-a hybrid microphone preamplifiers
-  **FULLY BALANCED INSERTS**  
Get direct access to your outboard processing!
-  **PRISTINE CONVERTER TECHNOLOGY**  
2-in 6-out 24-Bit 96kHz AD/DA system + ADAT i/o
-  **CONSOLE STYLE MONITOR CONTROLLER FUNCTIONALITY**  
Mono, polarity, dim, cut, speaker switching, talkback & cuemix
-  **USB2.0 CLASS COMPLIANT**  
Plug & play CoreAudio (Mac OSX) operation\*
-  **HIGH QUALITY ALL-METAL CONSTRUCTION**  
Sturdy, sleek & sexy desktop package - hands on control

\*Windows support in development

connect with us.



facebook.com/audient  
twitter.com/audientworld  
youtube.com/audienthampshire

[www.audient.com](http://www.audient.com)



- ▷ DSP LOW LATENCY MIXER APPLICATION\*  
Build monitor mixes & 2 stereo cue mixes
  - ▷ CONFIGURABLE CHANNEL VIEWS  
Maximise screen real estate
  - ▷ ASSIGNABLE TALKBACK INPUT  
Talk to your artists quickly and clearly
  - ▷ CUSTOMISE YOUR CONTROL SURFACE  
Assign various functions to F1, F2 & F3
  - ▷ PROGRAMMABLE DIM & ALT SPEAKERS  
Set level [dB] for dim and alternative outputs
  - ▷ FLEXIBLE & SIMPLE ROUTING MATRIX  
Route outputs and save/recall settings
- Mac OSX supported on release  
\*Windows support in development

iD22 will transform your DAW into a world-class recording system by connecting directly to your microphones, computer and monitors.

iD22 provides two classic *audient* microphone preamplifiers, ALL NEW pristine AD/DA converters that have been designed to deliver impeccable detail and impressive depth during both tracking & mixing. iD22 is expandable via ADAT i/o - perfect for partnering with an ASP008 for 10-ch recording [total 10-in, 12-out + headphones]. Our console-style monitor controller functionality and USB2.0 connectivity complete the ergonomic desktop package.

Features include:

- 2-in, 6-out high performance 24-bit/96kHz AD/DA converters
- 2 superb class-a mic preamplifiers & 1 discrete JFET instrument input
- Fully balanced insert points for integrating outboard gear
- High current headphone amplifier fed by an independant DAC
- 4 assignable line outputs for monitoring & processing
- User defined monitoring functionality with hardware control
- USB2.0 class compliant connectivity with integrated DSP mixer



Superb *audient* mic preamps



Pristine class leading AD/DA



Hardware monitor control



Programmable function keys



HANDS ON CONTROL



ERGONOMIC DESKTOP ENCLOSURE



KENSINGTON LOCK

